

## uTrust 2920 F

Bluetooth Contact Smart Card Reader



■ **COMPACT**

Lightweight, unique design

■ **VERSATILE**

Designed for mobile and desktop devices

■ **CONVENIENT**

Portable, Bluetooth-enabled, and features activity LED

Identiv's ISO/IEC7816-compatible uTrust 2920 F Bluetooth Contact Smart Card Reader provides a mobile, cable-free solution for secure multi-platform access to web-based email, portals, and collaboration sites authenticated to approved smart cards.

**Features and Benefits:**

- Enables the use of smart cards to eliminate complex passwords and password management
- Includes the added security of two-factor authentication
- All-platform compatible smart card reader can be used with desktop and mobile systems
- Rechargeable 350mAh Li battery

PARAMETER	UTRUST 2920 F
Host Interfaces	Micro USB Type A(CCID Standard)
Transmission Speed	12Mbps (USB 2.0 Full Speed)
Smart Card Interface	
Supported Tag ICs	All major ISO/IEC 7816 compliant smart card IC support
Smart Card Protocols	T=0, T=1
Smart Card Interface Speed	10753bps~625kbps (when supported by card)
Smart Card Types	ID-1, Class A, B, and C smart cards
Contact Type	8-pin ID-1 sliding contact
Driver and Software	
Contact Type	<ul style="list-style-type: none"> <li>• Windows</li> <li>• MacOS</li> <li>• Linux</li> <li>• UNIX</li> <li>• Android</li> <li>• iOS</li> </ul>
Software	<ul style="list-style-type: none"> <li>• PC/SC Lite</li> <li>• WINS CARD API</li> <li>• CCID</li> </ul>

PARAMETER		UTRUST 2920 F
Driver and Software		
PC/SC Driver	<ul style="list-style-type: none"> <li>• Windows</li> <li>• MacOS</li> <li>• Linux</li> <li>• UNIX</li> <li>• Android</li> <li>• iOS</li> </ul>	
Software	<ul style="list-style-type: none"> <li>• PC/SC Lite</li> <li>• WINS CARD API</li> <li>• CCID</li> </ul>	
Operating Conditions		
Power Supply	USB port 5V DC in connected mode, and to recharge battery	
Dimensions	85 x 64 x 13.5 mm (3.35 x 2.52 x 0.53 in)	
Weight	37 g ± 5% (0.081 lb ± 5%)	
Operating Temperature Range	0° to 60°C (32° to 122°F)	
Operating Humidity Range	Up to 90% RH non-condensing	
Durability	100,000 insertions	
Connector	0.8 m USB cable with USB type A connector	
Status Indicator	LED (Blue, Red, Yellow, Green)	
Battery	800mAh, rechargeable	
Power Consumption	Power off: 5µA	
	Standby: <50mA	
	Full speed current: <180mA	
Supported Standards		
Card Reader Standard	ISO-7816 Class A, B, C ( 5V, 3V,1.8V); EMV Level 1; PC/SC; USB 2.0; CCID	
API Standard	PC/SC Lite/WINS CARD API	
Bluetooth Standard	Bluetooth® 3.0 and 4.0	
Certifications and Compliances		
Functional Approvals	CE/FCC/EMV Level 1/LTIC/BSMI/NFC Forum/TELEC/Bluetooth® Smart	
Environmental Approvals	RoHS	
Applications	COMING SOON: Support for Sub Rosa/Sub Rosa Pro	
Product Part Number	905597	

Identiv (NASDAQ: INVE) is a global provider of physical security and secure identification. Identiv's products, software, systems, and services address the markets for physical and logical access control, video analytics and a wide range of RFID-enabled applications. Customers in the government, enterprise, consumer, education, healthcare, and banking, retail, and transportation sectors rely on Identiv's access and identification solutions. Identiv's mission is to secure the connected physical world: from perimeter to desktop access, and from the world of physical things to the Internet of Everything.

Identiv has offices worldwide. Addresses and phone numbers are listed at [identiv.com/contact](http://identiv.com/contact). For more information, visit [identiv.com](http://identiv.com) or email [sales@identiv.com](mailto:sales@identiv.com).

Technical data is subject to change without notice.

Copyright © 2019 Identiv, Inc. | All rights reserved. This document is Identiv public information.

Revision/Date of Release: 2019-10-23